

Process Heat > Hot air blower > MISTRAL

MISTRAL

For great heat in a confined space. Handy, also to reach into the most inaccessible places. Reliable, economical and powerful device, With brushless, high speed and compact motor. Predestined for continuous operation in harsh industrial environments.



- Brushless blower motor for continuous operation
- Light and handy
- Deployable as a built-in device and a hand tool
- Temperature manually adjustable
- Large air flow and high temperature
- Integrated device and heating element protection
- Works in every fitting position
- Wide range of accessories

SPECIFICATIONS

MISTRAL 120 V

Voltage	V~	120
Power consumption	W	2700
Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	350
Pressure static	Pa	2500 (25 mbar)
Size heater tube	mm	Ø 50
Weight	kg	1.5 (with 3 m cord)
Size (L x ø)	mm	320 x 95, handle Ø 64

Marking of conformity



Approval mark



Certification scheme




CCA

Protection class II




Process Heat > Hot air blower > MISTRAL

MISTRAL 200 V

Voltage	V~	200
Power consumption	W	3000
Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	350
Pressure static	Pa	2500 (25 mbar)
Size heater tube	mm	Ø 50
Weight	kg	1.5 (with 3 m cord)
Size (L x ø)	mm	320 x 95, handle Ø 64
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		

MISTRAL 230 V 2300 W

Voltage	V~	230
Power consumption	W	2300
Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	350
Pressure static	Pa	2500 (25 mbar)
Size heater tube	mm	Ø 50
Weight	kg	1.5 (with 3 m cord)
Size (L x ø)	mm	320 x 95, handle Ø 64
Marking of conformity		

Process Heat > Hot air blower > MISTRAL

Approval mark



Certification scheme

CCA

Protection class II



MISTRAL 230 V 3400 W

Voltage	V~	230
Power consumption	W	3400
Frequency	Hz	50 / 60
Temperature	°C	20 – 650
Air flow (20°C)	l/min	350
Pressure static	Pa	2500 (25 mbar)
Size heater tube	mm	Ø 50
Weight	kg	1.5 (with 3 m cord)
Size (L x Ø)	mm	320 x 95, handle Ø 64

Marking of conformity



Approval mark



Certification scheme

CCA

Protection class II



Process Heat > Hot air blower > MISTRAL

ACCESSORIES



Wide slot nozzle 150 x 12 mm push-fit on ELECTRON, LHS 40S, 40L, MISTRAL
107.270 - Wide slot nozzle 150 x 12 mm, push-fit



Folding reflector 72 x 70 mm push-fit on ELECTRON, LHS 40S, 40L, MISTRAL
107.331 - Folding reflector 72 x 70 mm, push-fit



Tubular nozzle for LHS 40S, 40L, MISTRAL
107.257 - Tubular nozzle, length 600 mm
Length of air outlet slot 420 mm,
push-fit



Extension nozzle for LHS 40S, 40L, MISTRAL
107.255 - Extension nozzle 36.5 x 160 mm, push-fit



Angled nozzle \varnothing 50 for LHS 40S, 40L, MISTRAL
107.256 - Angled nozzle \varnothing 50 mm
shank length 160 x 100 mm,
push-fit



Wide slot nozzle 70 x 10 mm push-fit on ELECTRON, LHS 40S, 40L
107.258 - Wide slot nozzle 70 x 10 mm, push-fit




Folding reflector 125 x 22mm push-fit on ELECTRON
107.330 - Folding reflector 125 x 22 mm, push-fit

Process Heat > Hot air blower > MISTRAL




Folding reflector 60 x 75mm push-fit on ELECTRON

107.328 - Folding reflector 60 x 75 mm, push-fit




Shell reflector 45 x 250 mm push-fit on ELECTRON

107.340 - Shell reflector 45 x 250 mm, push-fit



Sieve reflector 150 x 130mm push-fit

107.333 - Sieve reflector 150 x 130 mm, push-fit



Sieve reflector 85 x 85 mm push-fit on ELECTRON

107.327 - Sieve reflector 85 x 85 mm, push-fit