

IGNITER




The hot-air blower for installation in pellet and wood chip boilers.

- Connector plug directly on the device (easy removal and installation, fewer device configurations)
- Connection adapter for air hose located directly on the device with inner 1" thread (no extra accessories needed)
- New assembly support for perfect positioning in the furnace
- Additional pipe joint adapter with M14 thread for easy adaptation of the heat conduction lines and extensions
- Heating element protection with phototransistor and device protection via temperature protection circuit



SPECIFICATIONS




230/1600

Voltage	V~	230
Power consumption	W	1600
Frequency	Hz	50
Temperature	°C	600
Air flow (20°C)	l/min	230
Noise emission level LpA	dB	68
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		
Article Number		139.231




230/1100

Voltage	V~	230
---------	----	-----

Process Heat > Ignition blower > IGNITER

Power consumption	W	1100
Frequency	Hz	50
Temperature	°C	600
Air flow (20°C)	l/min	230
Noise emission level LpA	dB	68
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		
Article Number		140.711




230/600

Voltage	V~	230
Power consumption	W	600
Frequency	Hz	50
Temperature	°C	500
Air flow (20°C)	l/min	80
Noise emission level LpA	dB	58
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		
Article Number		139.232




120/1550

Voltage	V~	120
---------	----	-----

Process Heat > Ignition blower > IGNITER


Power consumption	W	1550
Frequency	Hz	60
Temperature	°C	600
Air flow (20°C)	l/min	230
Noise emission level LpA	dB	68
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		
Article Number		141.881

120/1100

Voltage	V~	120
Power consumption	W	1100
Frequency	Hz	60
Temperature	°C	600
Air flow (20°C)	l/min	230
Noise emission level LpA	dB	68
Weight	kg	1.0
Marking of conformity		
Approval mark		
Certification scheme		CCA
Protection class II		
Article Number		141.882

Process Heat > Ignition blower > IGNITER

ACCESSORIES




Adapter to
TRIAC S Economy heating pipe

142.359 -



Screw adapter
for M14 extensions

142.414 -



Air hose \varnothing 38 mm

107.286 - PVC air hose \varnothing 38 mm



Hose clip, \varnothing 38 mm and
 \varnothing 60 mm

107.287 - Hose clip for \varnothing 38 mm and
 \varnothing 60 mm air hose



Heating element for IGNITER

136.916 - 230 V ~ 1550 W

141.002 - 230 V ~ 1050 W

141.003 - 230 V ~ 550 W

136.918 - 120 V ~ 1500 W

141.005 - 120 V ~ 1050 W

141.006 - 120 V ~ 550 W